The Efficient, Versatile Air Compressor.

COMPRESSOR

The Arctic 1500 Series Compressor delivers up to 14 CFM at 6000 PSI as a customizable, high use solution. Designed to excel in commercial and industrial use.



Balanced Performance



Space-Saving, High-Capacity Design



Versatile for Multiple Applications





Product Comparison

| Model | PSI | CFM | HP | Stages | Series | |
|-----------|------|-----|-----|--------|----------------------|--|
| E4-20-A6 | 6000 | 24 | 20 | 4 | 2500 Series | |
| E4-15-A6 | 6000 | 18 | 15 | 4 | | |
| E4-10-A6 | 6000 | 14 | 10 | 4 | 1500 Series | |
| E4-7.5-A6 | 6000 | 9 | 7.5 | 4 | | |
| E3-7.5-A6 | 6000 | 8 | 7.5 | 3 | 1000 Series | |
| E3-7.5-A | 5000 | 9 | 7.5 | 3 | | |
| 04-10-A6 | 6000 | 9 | 10 | 4 | Open Frame Series | |
| 03-7.5-A6 | 6000 | 8 | 7.5 | 3 | | |
| 03-7.5-A | 5000 | 9 | 7.5 | 3 | | |

Electrical Requirements

All Arctic Compressors include an 8ft electrical cord and plug. The 1500 Series Enclosed Compressors require the following:

| 208/240V Connection | | | | 480V Connection | | |
|---------------------|-----|-------------|---------------|-----------------|----------|--|
| Phase | HP | Connector | Amperage | Connector | Amperage | |
| 3 | 7.5 | NEMA L15-30 | 30 Amp | NEMA L16-20 | 20 Amp | |
| 3 | 10 | NEMA L15-30 | 30 Amp | NEMA L16-20 | 20 Amp | |
| 1 | 7.5 | NEMA 6-50 | 50 Amp | | | |
| 1 | 10 | NEMA 6-50 | 50 Amp | | | |

Truly American-Made[™]

Reliability. Dependability. Simple.



CGA Grade E Quality Breathing Air

Our compressors deliver CGA Grade E breathing air, the gold standard for respiratory safety. This premium air quality not only meets but **exceeds** the stringent requirements set by regulatory bodies.

Air Purification

Filtration Technology

- Activated charcoal removes harmful gases and odors
- Carbon monoxide catalyst converts CO to harmless CO₂
- Ensures highest level of air purity for safe breathing

Moisture Control

- Reliable dryer filter
- Maintains dew point at or below -65°F (NFPA 1500 compliant)
- Prevents condensation and corrosion

What's Included

Low Noise Operation

- Fully Enclosed Sound Dampening Cabinet
- 76 dB Sound Level at 1 Meter

Easy Maintenance

- Lift Off Access Panels
- Automatic Condensate Drain System
- Easy Oil Maintenance Accessibility

Powerful Motor

 High-Efficiency Single or Three-Phase Electric Motor

Simple Lubrication System

- Splash Lubrication Oil System
- 3 qt Oil Capacity

Optional Upgrades

- CO Monitor with Automatic Shutdown
- Low Oil Level Automatic Shutdown
- High Temp with Automatic Shutdown
- Remote Start

Real-Time Monitoring

- Interstage Pressure Gauges
- Hour Meter
- Moisture/CO Visual Indicator

Durable Compressor Block

Radial Arctic Compressor Block, equipped with

- 10-Bladed High Velocity Fan
- Relief Valve on All Stages
- Aluminum Intercoolers
- Stainless Steel Aftercoolers
- Forged Steel Crankshaft
- Cast Iron Cylinders



Dimensions



| Door Position | Width | Height | Depth | Weight |
|----------------------|---------|--------|-------|--------|
| Closed | 38" 67" | | 24" | 700lbs |
| Open | 73" | 67" | 54" | 700lbs |



Warranty

All Arctic Compressors come with a standard 2-year warranty. Extend your coverage up to 5 years with our Silver or Gold Warranty options.



69 North 28th Street, Suite #500 Superior, WI 54880

(715) 718 - 3065 ArcticCompressor.com